

CamiFlex Lite

Camera over Hybrid fiber

One single Hybrid Optical cable is used to transport: Power, Video, Intercom, Tally and Remote.



Camera side



| | |
|----------------|--|
| Hybrid OPTICAL | Fischer FOH2-2 R13 plug, Fischer Fiber Optic Hybrid cable : FOH2-2 P01 Fiber length : over 200 meters |
| SDI In/Out | 3G/HD-SDI – SMPTE292M, SMPTE 424M |
| Genlock | CVBS |
| Remotes | 1 x Hirose 20p connexion for 3xRS and LANC |
| Tally LED | Red/Yellow LED with option external Red Tally plug on Jack 3.5mm |
| 12V DC OUTPUT | DC to Camera DC IN |
| Sizes | 175mm x 215mm x 42mm, with Kodak holder screw on bottom and tripod lock on top |

Remote side



| | |
|-----------------------|--|
| Hybrid OPTICAL | Fischer FOH2-2 R13 plug, Fischer Fiber Optic Hybrid cable : FOH2-2 P01 +48V DC on copper wire Fiber length : over 200 meters |
| SDI In/Out | 3G/HD-SDI – SMPTE292M, SMPTE 424M |
| Genlock | CVBS |
| Serial Remote 1, 2, 3 | 2 female SubD9 plug for serial connexions with Remote (such as: SONY RM-B150) 1 x MiniDIN6 connexion with JVC Remote (such as: RM-LP20) |
| LANC Remote | Mini jack plug (stereo) Ø2.5 mm |
| Tally input | Male SubD9 plug. Tally Red, Tally Yellow |
| 100-240V AC 50/60Hz | Worldwide IEC power plug |
| Sizes | 19" rack x 280 mm x 1U high |